

**标准规格**      **standard specification**

**中国电压规格**

| 型号                 | 电压 [V]  | 频率 [Hz] | 最大输出功率 [kW] | 额定电流 [A]  | 最大吐出风压 [kPa]        | 最大吐出风量 [m³/min] | 额定风压 [kPa] | 额定风量 [m³/min] | 耐热等级      | 噪音值 [dB(A)] | 吸吐口径 [mm,吋] | 概略重量 [kg] | 起动电流 [A] |                         |
|--------------------|---------|---------|-------------|-----------|---------------------|-----------------|------------|---------------|-----------|-------------|-------------|-----------|----------|-------------------------|
| 三相<br>标准型<br>内螺纹连接 | 220-380 | 50/60   | VFC088AF-S  | 0.06/0.08 | 0.38-0.22/0.4-0.23  | 3.73/4.85       | 0.47/0.56  | 1.96          | 0.25/0.35 | E           | 53.0/55.5   | PS1       | 5.5      | -                       |
|                    |         |         | VFC108AF-S  | 0.09/0.12 | 0.47-0.28/0.58-0.33 | 5.15/6.37       | 0.58/0.69  | 2.94          | 0.35/0.50 | E           | 52.5/56.5   | PS1       | 7        | 2.8-1.6/2.5-1.5         |
|                    |         |         | VFC208AF-S  | 0.17/0.28 | 1.3-0.75/1.3-0.74   | 6.67/9.02       | 0.90/1.09  | 2.94          | 0.64/0.84 | E           | 57.5/62.0   | PS1       | 8.5      | 6.8-4.0/6.1-3.6         |
|                    |         |         | VFC308AF-S  | 0.28/0.42 | 1.7-0.95/1.7-1.0    | 9.32/12.4       | 1.28/1.40  | 3.92          | 0.9/1.1   | E           | 58.0/62.0   | PS1 ¼     | 10.5     | 9.64-5.57/8.55-4.94     |
|                    |         |         | VFC408AF-S  | 0.55/0.85 | 2.9-1.7/3.4-2.0     | 10.4/14.1       | 2.0/2.5    | 4.90          | 1.45/1.95 | B           | 65.5/69.5   | PS1 ½     | 19.5     | 21.8-12.6/19.7-11.5     |
|                    |         |         | VFC508AF-S  | 1.3/1.9   | 5-2.9/6.7-3.9       | 14.7/19.6       | 3.4/4      | 6.86          | 2.4/3.0   | B           | 70.5/74.5   | PS1 ½     | 32       | 41.8-24.9/37.9-22.5     |
|                    |         |         | VFC608AF-S  | 2.3/3.4   | 9-5.2/11.5-6.8      | 21.1/27.5       | 4.2/5.5    | 9.81          | 3.2/4.4   | B           | 70.0/74.5   | PS2       | 50       | 94.3-54.1/77.6-45.6     |
|                    |         |         | VFC708AF-S  | 3.3/5.0   | 13.5-7.9/19-11      | 21.6/28.4       | 6.2/7.2    | 9.81          | 4.4/5.7   | F           | 75.0/79.5   | NPSC2     | 85       | 120-69/106-61           |
|                    |         |         | VFC808AF-S  | 5.5/7.5   | 18-10.5/25-14.5     | 25.5/33.3       | 8.7/10.3   | 9.81          | 6.3/8.5   | B           | 78.0/81.0   | NPSC2 ½   | 133      | 170.2-102.4/170.1-101.8 |
|                    |         |         | VFC908AF-S  | 11/15     | 27.5-16/41-23.5     | 25.5/31.4       | 13/15.5    | 14.7          | 7.5/10.8  | B           | 79.5/83.0   | PS3       | 200      | 352-205/308-180         |
| 三相<br>标准型<br>外螺纹连接 | 220-380 | 50/60   | VFC088A-S   | 0.06/0.08 | 0.38-0.22/0.4-0.23  | 3.73/4.85       | 0.47/0.56  | 1.96          | 0.25/0.35 | E           | 53.0/55.5   | φ32       | 5.5      | -                       |
|                    |         |         | VFC108A-S   | 0.09/0.12 | 0.47-0.28/0.58-0.33 | 5.15/6.37       | 0.58/0.69  | 2.94          | 0.35/0.50 | E           | 52.5/56.5   | PS1       | 7        | 2.8-1.6/2.5-1.5         |
|                    |         |         | VFC208A-S   | 0.17/0.28 | 1.3-0.75/1.3-0.74   | 6.67/9.02       | 0.90/1.09  | 2.94          | 0.64/0.84 | E           | 57.5/62.0   | PS1       | 8.5      | 6.8-4.0/6.1-3.6         |
|                    |         |         | VFC308A-S   | 0.28/0.42 | 1.7-0.95/1.7-1.0    | 9.32/12.4       | 1.28/1.40  | 3.92          | 0.9/1.1   | E           | 58.0/62.0   | PS1 ¼     | 10.5     | 9.64-5.57/8.55-4.94     |
|                    |         |         | VFC408A-S   | 0.55/0.85 | 2.9-1.7/3.4-2.0     | 10.4/14.1       | 2.0/2.5    | 4.90          | 1.45/1.95 | B           | 65.5/69.5   | PS1 ½     | 19.5     | 21.8-12.6/19.7-11.5     |
|                    |         |         | VFC508A-S   | 1.3/1.9   | 5-2.9/6.7-3.9       | 14.7/19.6       | 3.4/4      | 6.86          | 2.4/3.0   | B           | 70.5/74.5   | PS1 ½     | 32       | 41.8-24.9/37.9-22.5     |
|                    |         |         | VFC608A-S   | 2.3/3.4   | 9-5.2/11.5-6.8      | 21.1/27.5       | 4.2/5.5    | 9.81          | 3.2/4.4   | B           | 70.0/74.5   | PS2       | 50       | 94.3-54.1/77.6-45.6     |
|                    |         |         | VFC708A-S   | 3.3/5.0   | 13.5-7.9/19-11      | 21.6/28.4       | 6.2/7.2    | 9.81          | 4.4/5.7   | F           | 75.0/79.5   | NPSC2     | 85       | 120-69/106-61           |
|                    |         |         | VFC808A-S   | 5.5/7.5   | 18-10.5/25-14.5     | 25.5/33.3       | 8.7/10.3   | 9.81          | 6.3/8.5   | B           | 78.0/81.0   | NPSC2 ½   | 133      | 170.2-102.4/170.1-101.8 |
|                    |         |         | VFC908A-S   | 11/15     | 27.5-16/41-23.5     | 25.5/31.4       | 13/15.5    | 14.7          | 7.5/10.8  | B           | 79.5/83.0   | PS3       | 200      | 352-205/308-180         |
| 三相<br>静音型<br>内螺纹连接 | 220-380 | 50/60   | VFC088AN-S  | 0.06/0.08 | 0.38-0.22/0.4-0.23  | 3.73/4.85       | 0.47/0.56  | 1.96          | 0.25/0.35 | E           | 53.0/55.5   | φ32       | 5.5      | -                       |
|                    |         |         | VFC108AN-S  | 0.09/0.12 | 0.47-0.28/0.58-0.33 | 5.15/6.37       | 0.58/0.69  | 2.94          | 0.35/0.50 | E           | 52.5/56.5   | PS1       | 7        | 2.8-1.6/2.5-1.5         |
|                    |         |         | VFC208AN-S  | 0.17/0.28 | 1.3-0.75/1.3-0.74   | 6.67/9.02       | 0.90/1.09  | 2.94          | 0.64/0.84 | E           | 57.5/62.0   | PS1       | 8.5      | 6.8-4.0/6.1-3.6         |
|                    |         |         | VFC308AN-S  | 0.28/0.42 | 1.7-0.95/1.7-1.0    | 9.32/12.4       | 1.28/1.40  | 3.92          | 0.9/1.1   | E           | 58.0/62.0   | PS1 ¼     | 10.5     | 9.64-5.57/8.55-4.94     |
|                    |         |         | VFC408AN-S  | 0.55/0.85 | 2.9-1.7/3.4-2.0     | 10.4/14.1       | 2.0/2.5    | 4.90          | 1.45/1.95 | B           | 65.5/69.5   | PS1 ½     | 19.5     | 21.8-12.6/19.7-11.5     |
|                    |         |         | VFC508AN-S  | 1.3/1.9   | 5-2.9/6.7-3.9       | 14.7/19.6       | 3.4/4      | 6.86          | 2.4/3.0   | B           | 70.5/74.5   | PS1 ½     | 32       | 41.8-24.9/37.9-22.5     |
|                    |         |         | VFC608AN-S  | 2.3/3.4   | 9-5.2/11.5-6.8      | 21.1/27.5       | 4.2/5.5    | 9.81          | 3.2/4.4   | B           | 70.0/74.5   | PS2       | 50       | 94.3-54.1/77.6-45.6     |
|                    |         |         | VFC708AN-S  | 3.3/5.0   | 13.5-7.9/19-11      | 21.6/28.4       | 6.2/7.2    | 9.81          | 4.4/5.7   | F           | 75.0/79.5   | NPSC2     | 85       | 120-69/106-61           |
|                    |         |         | VFC808AN-S  | 5.5/7.5   | 18-10.5/25-14.5     | 25.5/33.3       | 8.7/10.3   | 9.81          | 6.3/8.5   | B           | 78.0/81.0   | NPSC2 ½   | 133      | 170.2-102.4/170.1-101.8 |
|                    |         |         | VFC908AN-S  | 11/15     | 27.5-16/41-23.5     | 25.5/31.4       | 13/15.5    | 14.7          | 7.5/10.8  | B           | 79.5/83.0   | PS3       | 200      | 352-205/308-180         |
| 三相<br>静音型<br>外螺纹连接 | 110-220 | 50/60   | VFC088PF-S  | 0.06/0.08 | 1.0-0.5/1.4-0.7     | 3.73/4.85       | 0.47/0.56  | 1.96          | 0.25/0.35 | E           | 53.0/55.5   | PS1       | 5.5      | 3.4-1.6/4.0-1.9         |
|                    |         |         | VFC108PF-S  | 0.09/0.12 | 1.3-0.65/1.6-0.8    | 5.10/6.86       | 0.58/0.69  | 2.94          | 0.35/0.50 | E           | 52.5/56.5   | PS1       | 7.5      | 8-3.8/9.5-4.6           |
|                    |         |         | VFC208PF-S  | 0.17/0.28 | 3.0-1.3/3.8-1.9     | 6.67/8.63       | 0.88/1.05  | 2.94          | 0.64/0.84 | E           | 57.5/62.0   | PS1       | 9.0      | 8.2-3.9/9.6-4.6         |
|                    |         |         | VFC308PF-S  | 0.25/0.38 | 3.8-1.9/5.2-2.6     | 9.61/12.0       | 1.25/1.45  | 3.92          | 0.9/1.1   | E           | 58.0/62.0   | PS1 ¼     | 11.5     | 11.2-5.9/13.4-7.0       |
|                    |         |         | VFC408PF-S  | 0.5/0.75  | 6.0-3.0/9.0-4.5     | 9.81/13.2       | 2.05/2.45  | 4.90          | 1.45/1.95 | B           | 65.5/69.5   | PS1 ½     | 21.5     | 19-9.6/22.5-11.5        |
|                    |         |         | VFC508PF-S  | 1.3/1.9   | 14-10.5/17-12.7     | 14.7/19.6       | 3.4/4.0    | 6.86          | 2.4/3.0   | B           | 70.5/74.5   | PS1 ½     | 44       | -                       |

注) 以上表示的机型是内螺纹的连接方式。

噪音是指开放时1.5m位置的数值。

日本电压规格

| 型号          | 电压 [V]          | 频率 [Hz]                   | 最大输出功率 [kW]                 | 额定电流 [A]         | 最大吐出风压 [kPa]  | 最大吐出风量 [m³/min]          | 额定风压 [kPa]  | 额定风量 [m³/min] | 耐热等级      | 噪音值 [dB(A)] | 吸吐口径 [mm,吋] | 额定重量 [kg]   | 启动电流 [A]                 |
|-------------|-----------------|---------------------------|-----------------------------|------------------|---------------|--------------------------|-------------|---------------|-----------|-------------|-------------|-------------|--------------------------|
| VFC088AF    | 200 / 200 / 220 | 50 / 60                   | 0.06 / 0.08                 | 0.37 / 0.42-0.40 | 3.73 / 4.85   | 0.47 / 0.56              | 1.96        | 0.25 / 0.35   | E         | 53.0 / 55.5 | PS1         | 5.5         | 2 / 2-2.2                |
| VFC108AF    |                 |                           | 0.09 / 0.12                 | 0.51 / 0.62-0.60 | 5.15 / 6.37   | 0.58 / 0.69              | 2.94        | 0.35 / 0.50   | E         | 52.5 / 56.5 | PS1         | 7.5         | 4.2 / 3.9-4.2            |
| VFC208AF    |                 |                           | 0.17 / 0.28                 | 1.4 / 1.4-1.4    | 6.67 / 9.02   | 0.90 / 1.09              | 2.94        | 0.64 / 0.84   | E         | 57.5 / 62.0 | PS1         | 9.0         | 9 / 8.1-9                |
| VFC308AF    |                 |                           | 0.28 / 0.42                 | 1.8 / 1.9-1.8    | 9.32 / 12.4   | 1.28 / 1.40              | 3.92        | 0.9 / 1.1     | E         | 58.0 / 62.0 | PS1 1/4     | 11          | 13 / 12-13.5             |
| VFC408AF    |                 |                           | 0.55 / 0.85                 | 3.1 / 3.7-3.6    | 10.4 / 14.1   | 2.0 / 2.5                | 4.90        | 1.45 / 1.95   | B         | 65.5 / 69.5 | PS1 1/2     | 19.5        | 27 / 25-27.5             |
| VFC508AF    |                 |                           | 1.3 / 1.9                   | 5.4 / 7.4-6.8    | 14.7 / 19.6   | 3.4 / 4.0                | 6.86        | 2.4 / 3.0     | B         | 70.5 / 74.5 | PS1 1/2     | 28.0        | 55 / 52-57               |
| VFC608AF    |                 |                           | 2.3 / 3.4                   | 10 / 13-12       | 21.1 / 27.5   | 4.2 / 5.5                | 9.81        | 3.2 / 4.4     | B         | 70.0 / 74.5 | PS2         | 44.0        | 98 / 89-98               |
| VFC088A     | 200 / 200 / 220 | 50 / 60                   | 0.06 / 0.08                 | 0.37 / 0.42-0.40 | 3.73 / 4.85   | 0.47 / 0.56              | 1.96        | 0.25 / 0.35   | E         | 53.0 / 55.5 | 32          | 5.5         | 2 / 2-2.2                |
| VFC108A     |                 |                           | 0.09 / 0.12                 | 0.51 / 0.62-0.60 | 5.15 / 6.37   | 0.58 / 0.69              | 2.94        | 0.35 / 0.50   | E         | 52.5 / 56.5 | 32          | 7.0         | 4.2 / 3.9-4.2            |
| VFC208A     |                 |                           | 0.17 / 0.28                 | 1.4 / 1.4-1.4    | 6.67 / 9.02   | 0.90 / 1.09              | 2.94        | 0.64 / 0.84   | E         | 57.5 / 62.0 | 32          | 8.5         | 9 / 8.1-9                |
| VFC308A     |                 |                           | 0.28 / 0.42                 | 1.8 / 1.9-1.8    | 9.32 / 12.4   | 1.28 / 1.40              | 3.92        | 0.9 / 1.1     | E         | 58.0 / 62.0 | 38          | 10.5        | 13 / 12-13.5             |
| VFC408A     |                 |                           | 0.55 / 0.85                 | 3.1 / 3.7-3.6    | 10.4 / 14.1   | 2.0 / 2.5                | 4.90        | 1.45 / 1.95   | B         | 65.5 / 69.5 | 50, PT1 1/2 | 19          | 27 / 25-27.5             |
| VFC508A     |                 |                           | 1.3 / 1.9                   | 5.4 / 7.4-6.8    | 14.7 / 19.6   | 3.4 / 4.0                | 6.86        | 2.4 / 3.0     | B         | 70.5 / 74.5 | 50, PT1 1/2 | 31.5        | 55 / 52-57               |
| VFC608A     |                 |                           | 2.3 / 3.4                   | 10 / 13-12       | 21.1 / 27.5   | 4.2 / 5.5                | 9.81        | 3.2 / 4.4     | B         | 70.0 / 74.5 | 63, PT2     | 49          | 98 / 89-98               |
| *VFC708A    |                 |                           | 3.3 / 5.0                   | 15 / 21-19       | 21.6 / 28.4   | 6.2 / 7.2                | 9.81        | 4.4 / 5.7     | F         | 75.0 / 79.5 | PS2         | 84          | 145 / 128-141            |
| *VFC808A    |                 |                           | 5.5 / 7.5                   | 20 / 28-26       | 25.5 / 33.3   | 8.7 / 10.3               | 9.81        | 6.3 / 8.5     | B         | 78.0 / 81.0 | PS2 1/2     | 132         | 227 / 193-212            |
| *VFC908A    |                 |                           | 11 / 15                     | 30 / 45-41       | 25.5 / 31.4   | 13 / 15.5                | 14.7        | 7.5 / 10.8    | B         | 79.5 / 83.0 | PS3         | 200         | 406 / 351-387            |
| VFC088A-4Z  |                 |                           | 380 / 400 / 415 / 400 / 440 | 50 / 60          | 0.06 / 0.08   | 0.2-0.2-0.21 / 0.22-0.21 | 3.73 / 4.85 | 0.47 / 0.56   | 1.96      | 0.25 / 0.35 | E           | 53.0 / 55.5 | 32                       |
| VFC108A-4Z  | 0.09 / 0.12     | 0.27-0.26-0.26 / 0.31-0.3 |                             |                  | 5.15 / 6.37   | 0.58 / 0.69              | 2.94        | 0.35 / 0.50   | E         | 52.5 / 56.5 | 32          | 7.0         | 2-2.1-2.1 / 1.9-2.1      |
| VFC208A-4Z  | 0.17 / 0.28     | 0.6-0.63-0.66 / 0.7-0.68  |                             |                  | 6.67 / 9.02   | 0.90 / 1.09              | 2.94        | 0.64 / 0.84   | E         | 57.5 / 62.0 | 32          | 8.5         | 3.6-3.9-4 / 3.4-3.7      |
| VFC308A-4Z  | 0.28 / 0.42     | 0.86-0.9-0.95 / 0.95-0.9  |                             |                  | 9.32 / 12.4   | 1.28 / 1.40              | 3.92        | 0.91 / 1.1    | E         | 58.0 / 62.0 | 38          | 10.5        | 5.9-6.5-6.7 / 6.1-6.7    |
| VFC408A-4Z  | 0.55 / 0.85     | 1.7-1.6-1.5 / 1.9-1.8     |                             |                  | 10.4 / 14.1   | 2.0 / 2.5                | 4.90        | 1.45 / 1.95   | B         | 65.5 / 69.5 | 50, PT1 1/2 | 19.5        | 13-13.5-14 / 12.5-14     |
| VFC508A-4Z  | 1.3 / 1.9       | 2.9-2.7-2.6 / 3.7-3.4     |                             |                  | 14.7 / 19.6   | 3.4 / 4.0                | 6.86        | 2.4 / 3.0     | E         | 70.5 / 74.5 | 50, PT1 1/2 | 31.5        | 26.5-27.5-28.5 / 26-28.5 |
| VFC608A-4Z  | 2.3 / 3.4       | 5.3-5.0-4.9 / 6.5-6       |                             |                  | 21.1 / 27.5   | 4.2 / 5.5                | 9.81        | 3.2 / 4.4     | E         | 70.0 / 74.5 | 63, PT2     | 49          | 46-49-51 / 44-49         |
| *VFC708A-4Z | 3.3 / 5.0       | 7.5-7.5-7.3 / 10.5-9.5    |                             |                  | 21.6 / 28.4   | 6.2 / 7.2                | 9.81        | 4.4 / 5.7     | F         | 75.0 / 79.5 | PS2         | 84          | 69-73-75 / 64-71         |
| *VFC808A-4Z | 5.5 / 7.5       | 10.6-10-9.7 / 14-13       |                             |                  | 25.5 / 33.3   | 8.7 / 10.3               | 9.81        | 6.3 / 8.5     | B         | 78.0 / 81.0 | PS2 1/2     | 132         | 108-113-118 / 96-106     |
| VFC088AN    | 200 / 200 / 220 | 50 / 60                   | 0.06 / 0.08                 | 0.37 / 0.42-0.40 | 3.73 / 4.85   | 0.47 / 0.56              | 1.96        | 0.25 / 0.35   | E         | 50.5 / 53.0 | 32          | 7.5         | 2 / 2-2.2                |
| VFC108AN    |                 |                           | 0.09 / 0.12                 | 0.51 / 0.62-0.60 | 5.15 / 6.37   | 0.58 / 0.69              | 2.94        | 0.35 / 0.50   | E         | 49.5 / 51.5 | 32          | 8.5         | 4.2 / 3.9-4.2            |
| VFC208AN    |                 |                           | 0.17 / 0.28                 | 1.4 / 1.4-1.4    | 6.67 / 9.02   | 0.90 / 1.09              | 2.94        | 0.64 / 0.84   | E         | 55.5 / 59.0 | 32          | 12.0        | 9 / 8.1-9                |
| VFC308AN    |                 |                           | 0.28 / 0.42                 | 1.8 / 1.9-1.8    | 9.32 / 12.4   | 1.28 / 1.40              | 3.92        | 0.9 / 1.1     | E         | 55.5 / 59.5 | 38          | 12.0        | 13 / 12-13.5             |
| VFC408AN    |                 |                           | 0.55 / 0.85                 | 3.1 / 3.7-3.6    | 10.4 / 14.1   | 2.0 / 2.5                | 4.90        | 1.45 / 1.95   | B         | 62.0 / 66.0 | 50, PT1 1/2 | 22.0        | 27 / 25-27.5             |
| VFC508AN    |                 |                           | 1.3 / 1.9                   | 5.4 / 7.4-6.8    | 14.7 / 19.6   | 3.4 / 4.0                | 6.86        | 2.4 / 3.0     | B         | 66.0 / 69.5 | 50, PT1 1/2 | 3.6         | 55 / 52-57               |
| VFC608AN    |                 |                           | 2.3 / 3.4                   | 10 / 13-12       | 21.1 / 27.5   | 4.2 / 5.5                | 9.81        | 3.2 / 4.4     | B         | 67.5 / 70.5 | 63, PT2     | 53          | 98 / 89-98               |
| *VFC708AN   |                 |                           | 3.3 / 5.0                   | 15 / 21-19       | 21.6 / 28.4   | 6.2 / 7.2                | 9.81        | 4.4 / 5.7     | F         | 70.5 / 74.5 | PS2         | 100         | 145 / 128-141            |
| *VFC808AN   |                 |                           | 5.5 / 7.5                   | 20 / 28-26       | 25.5 / 33.3   | 8.7 / 10.3               | 9.81        | 6.3 / 8.5     | B         | 74.0 / 75.0 | PS2 1/2     | 144         | 227 / 193-212            |
| *VFC908AN   |                 |                           | 11 / 15                     | 30 / 45-41       | 25.5 / 31.4   | 13 / 15.5                | 14.7        | 7.5 / 10.8    | B         | 76.0 / 79.5 | PS3         | 219         | 406 / 351-387            |
| VFC088P     |                 |                           | 100                         | 50 / 60          | 0.023 / 0.035 | 0.46 / 0.6               | 1.62 / 2.26 | 0.42 / 0.48   | 0.981     | 0.20 / 0.30 | E           | 52.5 / 56.0 | 32                       |
| VFC088P     | 100 / 100 / 110 | 0.06 / 0.08               | 1.3 / 1.4-1.3               |                  | 3.73 / 4.85   | 0.47 / 0.56              | 1.96        | 0.25 / 0.35   | E         | 53.0 / 55.5 | 32          | 5.5         | 4 / 3.8-4.2              |
| VFC108P     |                 | 0.09 / 0.12               | 1.5 / 2.0-1.9               |                  | 5.10 / 6.86   | 0.58 / 0.69              | 2.94        | 0.35 / 0.50   | E         | 52.5 / 56.5 | 32          | 7.5         | 9.4 / 9.2-10             |
| VFC208P     |                 | 0.17 / 0.28               | 4.5 / 4.4-4.2               |                  | 6.67 / 8.63   | 0.86 / 1.05              | 2.94        | 0.64 / 0.84   | E         | 57.5 / 62.0 | 32          | 9.0         | 14.5 / 13-14.5           |
| VFC308P     |                 | 0.25 / 0.38               | 5.0 / 5.8-5.6               |                  | 9.61 / 12.0   | 1.25 / 1.45              | 3.92        | 0.9 / 1.1     | E         | 58.0 / 62.0 | 38          | 11.5        | 18.5 / 17.5-19.5         |
| VFC408P     |                 | 0.50 / 0.75               | 7.0 / 11.0-10.0             |                  | 9.81 / 13.2   | 2.05 / 2.45              | 4.90        | 1.45 / 1.95   | B         | 65.5 / 69.5 | 50, PT1 1/2 | 21.5        | 37 / 33-37               |
| VFC508P     |                 | 200 / 200 / 220           | 1.3 / 1.9                   |                  | 8.0 / 12-11   | 14.7 / 19.6              | 3.4 / 4.0   | 6.86          | 2.4 / 3.0 | B           | 70.5 / 74.5 | 50, PT1 1/2 | 44                       |
| VFC088PN    | 100 / 100 / 110 | 50 / 60                   | 0.06 / 0.08                 | 1.3 / 1.4-1.3    | 3.73 / 4.85   | 0.47 / 0.56              | 1.96        | 0.25 / 0.35   | E         | 49.0 / 52.5 | 32          | 7.5         | 4 / 3.8-4.2              |
| VFC108PN    |                 |                           | 0.09 / 0.12                 | 1.5 / 2.0-1.9    | 5.10 / 6.86   | 0.58 / 0.69              | 2.94        | 0.35 / 0.50   | E         | 48.5 / 51.5 | 32          | 8.5         | 9.4 / 9.2-10             |
| VFC208PN    |                 |                           | 0.17 / 0.28                 | 4.5 / 4.4-4.2    | 6.67 / 8.63   | 0.86 / 1.05              | 2.94        | 0.64 / 0.84   | E         | 55.0 / 59.5 | 32          | 12.0        | 14.5 / 13-14.5           |
| VFC308PN    |                 |                           | 0.25 / 0.38                 | 5.0 / 5.8-5.6    | 9.61 / 12.0   | 1.25 / 1.45              | 3.92        | 0.9 / 1.1     | E         | 55.5 / 59.5 | 38          | 12.0        | 18.5 / 17.5-19.5         |
| VFC408PN    |                 |                           | 0.5 / 0.75                  | 7.0 / 11.0-10.0  | 9.81 / 13.2   | 2.05 / 2.45              | 4.90        | 1.45 / 1.95   | B         | 62.5 / 66.5 | 50, PT1 1/2 | 22.0        | 37 / 33-37               |

注) 以上※印の機種は内螺纹の接続方式。

噪音是指开放时1.5m位置的数值。